

Model No	SW2495T	Price(usd)	Sample	100-500pcs	1-3K	3-5K	,+5K
Brand		Lead time					
Product type	Android Tablet	MOQ					
Product Description	24" Digital Signage	Payment					
Date	30.03.2024						



System	CPU	RK3588S2 Quad core cortex A55+Quad core cortex A76	
	RAM	4GB	
	Internal memory	64GB <b>Optional 128GB</b>	
Display	Operation system	Android 13	
	Panel Size	23.8"LCD	
	Panel Type	IPS	
	Resolution	1920*1080	
	Display Colors	16.7M Colors	
	Color Gamut	72% NTSC	
	Display mode	Normally black	
	Viewing angle	R/L 89/89, U/D 89/89	
	Contrast ratio	1000:1	
	Response Time	9ms	
	Back-light Type	Eled	
	Touch	Luminance	250cdm2
Aspect Ratio		,16:9	
Network	Model Type	In cell touch	
	Number of points	10-Point	
Interface	Interface for touch	HID-USB	
	WiFi	IEEE 802.11a/b/g/n/ac/ax with Mu-MIMO standard	
Media plays	Bluetooth	Bluetooth 5.3	
	USB	USB 2.0 Host	
	USB	USB 3.0 Host	
	Type-C	Multi-function interface : Default Type-c full function ,Connecting to HDMI IN, Optional external device with touch function	
Other	HDMI IN	Support 800*600,1024*768,1280*720,1280*800,1280*1024,1366*768,1600*900,1920*1080,3840*2160, etc	
	Power Jack	DC power input	
	Video format	MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9,MVC,AV1, etc., support up to 8K@60fps	
	Audio format	MP3/WMA/AAC/WAV/OGG, etc	
	Photo	JPEG/PNG/GIF,etc	
	Product Colors	white/Black	
	VESA	100mm*100mm	
	Button	Power/Vol+/Vol-	
	G-sensor	Support 90 degrees	
	Speaker	4Ω/5W*2	
Battery pack	Microphone	Standard dual Microphone , Support noise reduction and echo cancellation	
	NFC	<b>Optional , 13.56MHz, ISO/IEC 18092, ISO/IEC 21481, ISO/IEC 14443 A&amp;B, ISO/IEC 15693, Japanese Industrial Standard (JIS) (X) 6319-4, MIFARE Classic encrypted tags and cards</b>	
	Camera	<b>Optional External USB type camera ( vertical portrait , 8MP )</b>	
	Language	Multi-language	
	Certificates	CCC/CE/FCC	
	battery Typ	Li-ion of 18650	
	battery pack capacity	14.4V/5200mAh	
	Full battery life	3-4H	
	Construction	Function	Tilting angle ( Forward tilt-Lean back) -20° ~ 20° ±3°
			Turning ( Left and Right ) -15° ~ 15° ±3°
		Rotating ( Clockwise ) 90°	
		Lifting ( up-down) 180mm	
Working Surrounding	Working Temperature	0℃---40℃	
	Storage Temperature	-20℃---60℃	
	Working Humidity	20~80%RH	
	Storage Humidity	10~95%RH	
Accessories	Adapter	18V/3A	
	AC Cable	L=1.5m	
	Screws	BM 3x16*5 , PWM 3x5*2 , PWM 4x6*3 , PM 4x16*4	
	Cover	*1	
	Screwdriver	*1	
	User manual	*1	
	USB cable	<b>*1Optional</b>	
	Foot pad	*4	
Remote	*1(Bluetooth voice version)		

