

Model No	SW2195T	Price(usd)	Sample	100-500pcs	1-3K	3-5K	,+5K
Brand		Lead time					
Product type	Android Tablet	MOQ					
Product Description	21" Digital Signage	Payment					
Date	26.03.2024						



System	CPU	RK3588S2 Quad core cortex A55+Quad core cortex A76
	RAM	8GB
	Internal memory	128GB
Display	Operation system	Android 13
	Panel Size	21.5"LCD
	Panel Type	IPS
	Resolution	1920*1080
	Display Colors	16.7M Colors
	Color Gamut	72% NTSC
	Display mode	Normally black
	Viewing angle	R/L 89/89, U/D 89/89
	Contrast ratio	3000:1
	Response Time	7ms
	Back-light Type	Eled
	Touch	Luminance
Aspect Ratio		,16:9
Network	Model Type	Capacitive touch screen
	Number of points	10-Point
Interface	Interface for touch	USB
	WiFi	IEEE 802.11a/b/g/n/ac/ax with Mu-MIMO standard
Media plays	Bluetooth	Bluetooth 5.3
	USB	USB 2.0 Host
	USB	USB 3.0 Host
	Type-C	Full Function (Except for charging function)
Other	HDMI IN	Support 800*600,1024*768,1280*720,1280*800,1280*1024,1366*768,1600*900,1920*1080,3840*2160, etc
	Power Jack	DC power input
	Video format	MPEG-1,MPEG-2,MPEG-4,H.265,H.264,VC-1,VP8,VP9,MVC,AV1, etc., support up to 8K@60fps
	Audio format	MP3/WMA/AAC/WAV/OGG, etc
	Photo	JPEG/PNG/GIF,etc
	Product Colors	white/Black
	VESA	100mm*100mm
	Button	Power/Vol+/Vol-
	G-sensor	Support 90 degrees
	Speaker	4Ω/5W*2
Battery pack	Microphone	Standard dual Microphone , Support noise reduction and echo cancellation
	NFC	Optional NXP. 13.56MHz. ISO/IEC 18092, ISO/IEC 21481, ISO/IEC 14443 A&B, ISO/IEC 15693, Japanese Industrial Standard (JIS) (X) 6319-4, MIFARE Classic encrypted tags and cards
Construction	Camera	Optional External USB type camera (vertical portrait , 8MP)
	Language	Multi-language
Working Surrounding	Certificates	CCC
	battery Typ	Li-ion of 18650
	battery pack capacity	14.4V/5200mAh
	Full battery life	3-4H
Accessories	Function	Tilting angle (Forward tilt-Lean back) -20° ~ 20° ±3° Turning (Left and Right) -15° ~ 15° ±3° Rotating (Clockwise) 90° Lifting (up-down) 180mm
	Working Temperature	0℃---40℃
	Storage Temperature	-20℃---60℃
	Working Humidity	20~80%RH
Accessories	Storage Humidity	10~95%RH
	Adapter	18V/3A
	AC Cable	L=1.5m
	Screws	BM 3x16*5 , PWM 3x5*2 , PWM 4x6*3 , PM 4x16*4
	Cover	*1
	Screwdriver	*1
	User manual	*1
	USB cable	*1Optional
Foot pad	*4	
Remote	*1(Bluetooth voice version)	