

Vormatic Digital Display Double Catalog



- Ultra Slim Enclosure Designed,
- Surface Designed with High Transparency Tempered Glass, Aluminum Alloy Frame Cover
- Built-in Android system & Windows (Optional)
- Compact design for multiple installations ways, easy installation .
- support 10 points IR/ Capacitive touch/Non-touch
- Fanless and Low-power System, Support 24/7 non stop working
- Color:Black option

Panel Information

Panel Size	43"	49"	55"
Panel Type	a-Si TFT-LCD	a-Si TFT-LCD	a-Si TFT-LCD
Active area(mm)	941.184 *529.416	1073.78*604	1209.6 × 680.4
Resolution	1920 x 1080	1920 x 1080	1920 x 1080
Brightness	350 Nits	350 Nits	350 Nits
Contrast Ratio	1200:1	1200:1	1200:1
Viewing Angle(Typ.)	89/89/89/89	89/89/89/89	89/89/89/89
Aspect Ratio	16:9	16:9	16:9
LED Life Time	50,000 hours	50,000 hours	50,000 hours
Touch Features	10 points IR/ Capacitive touch	10 points IR/ Capacitive touch	10 points IR/ Capacitive touch

Panel Information

Panel Size	65"	75"	85"
Panel Type	a-Si TFT-LCD	a-Si TFT-LCD	a-Si TFT-LCD
Active area(mm)	1428.48×803.52	1649.66×927.936	1872×1053
Resolution	1920 x 1080	3840 x 2160	3840 x 2160
Brightness	350 Nits	350 Nits	350 Nits
Contrast Ratio	1200:1	1200:1	1200:1
Viewing Angle(Typ.)	89/89/89/89	89/89/89/89	89/89/89/89
Aspect Ratio	16:9	16:9	16:9
LED Life Time	50,000 hours	50,000 hours	50,000 hours
Touch Features	10 points IR/ Capacitive touch	10 points IR touch	10 points IR touch

Motherboard

Operating System	Windows 10	Android 11
CPU	I5	Quad-Core ARM Cortex-A55 2.0GHz RK3568
Memory	4G	2G
Storage	128G SSD	16G
Network	Wifi, RJ45	Wifi, RJ45
I/O Ports	USB2.0*2/ USB3.0*2/ HDMI out*1/ VGA out*1/ RJ45 Lan port*1/ Speaker out*1/ Mic in*1	USB 3.0 *2, , RJ45 *1, HDMI Out *1, earphone port*1 Standard MicroSD Card Slot *1 (Support Max 128G)
Language	English	English
Speakers	5W x2	5W x2

Environment

Operating System	0°C ~ 50°C
Storage System	-20°C ~ 60°C

Power

Power Supply	96~220 V
Rated Frequency	50/60Hz