

Model No	SW3295T	Price(usd)	Sample	100-500pcs	1-3K	3-5K	,+5K
Brand		Lead time					
Product type	Android Tablet	MOQ					
Product Description	32" Digital Signage	Payment					
Date	30.03.2024						



System	CPU	RK3588S2 Quad core cortex A55+Quad core cortex A76
	RAM	8GB Optional 116GB
	Internal memory	128GB
	Operation system	Android 13
Display	Panel Size	32"LCD
	Panel Type	IPS
	Resolution	1920*1080
	Display Colors	16.7M Colors
	Color Gamut	72% NTSC
	Display mode	Normally black
	Viewing angle	R/L 89/89, U/D 89/89
	Contrast ratio	1000:1
	Response Time	8ms
	Back-light Type	Eled
	Luminance	250cdm2
Aspect Ratio	,16:9	
Touch	Model Type	In cell touch
	Number of points	10-Point
	Interface for touch	HID-USB
Network	WiFi	IEEE 802.11a/b/g/n/ac/ax with Mu-MIMO standard
	Bluetooth	Bluetooth 5.2
Interface	USB	USB 2.0 Host
	USB	USB 3.0 Host
	Type-C	Multi-function interface : Default Type-c full function ,Connecting to HDMI IN, Optional external device with touch function
	HDMI IN	Support 800*600,1024*768,1280*720,1280*800,1280*1024,1366*768,1600*900,1920*1080,3840*2160, etc
Media plays	Power Jack	DC power input
	Video format	MPEG-1,MPEG-2,MPEG-4,H.265,H.264,H.263,VC-1,VP8,VP9,MVC,AV1, etc., support up to 8K@60fps
	Audio format	MP3/WMA/AAC/WAV/OGG, etc
Other	Photo	JPEG/PNG/GIF,etc
	Product Colors	white/Black
	VESA	100mm*100mm
	Button	Power/Vol+/Vol-
	G-sensor	Support 90 degrees
	Speaker	4Ω/5W*2
	Microphone	Standard dual Microphone , Support noise reduction and echo cancellation
	NFC	Optional , 13.56MHz, ISO/IEC 18092, ISO/IEC 21481, ISO/IEC 14443 A&B, ISO/IEC 15693, Japanese Industrial Standard (JIS) (X) 6319-4, MIFARE Classic encrypted tags and cards
	Camera	Optional External USB type camera (vertical portrait , 8MP)
	Language	Multi-language
	Certificates	CCC/CE/FCC
Battery pack	battery Typ	Li-ion of 18650
	battery pack capacity	14.4V/6800mAh
	Full battery life	3-4H
Construction	Function	Tilting angle (Forward tilt-Lean back) -20° ~ 20° ±3°
		Turning (Left and Right) -15° ~ 15° ±3°
		Rotating (Clockwise) 90°
		Lifting (up-down) 180mm
Working Surrounding	Working Temperature	0℃---40℃
	Storage Temperature	-20℃---60℃
	Working Humidity	20~80%RH
	Storage Humidity	10~95%RH
Accessories	Adapter	18V/3A
	AC Cable	L=1.5m
	Screws	BM 3x16*5 , PWM 3x5*2 , PWM 4x6*3 , PM 4x16*4
	Cover	*1
	Screwdriver	*1
	User manual	*1
	USB cable	*1Optional
	Foot pad	*4
Remote	*1(Bluetooth voice version)	

